



Commercial Floor Care Equipment

## Quick Clean™ 1500 All Surface Cleaner

Features	Specifications	
<b>Product Name</b>	<b>Quick Clean™ 1500</b>	
<b>Model Number</b>	<b>609640 – U.S.</b>	<b>609799 - Canada</b>
<b>Body Construction</b> Caster: Wheel Type:	Rotationally-molded polyethylene 4 in (101mm) 12 in (304 mm) Solid Wheels	
<b>Solution Pump</b> Solution Pump Voltage: Solution Pump Amps: Solution Pump:	120 V 4.5 A 1 gpm/300 psi at high pressure; 1.5 gpm/45 psi at low pressure	
<b>Vacuum Motors (2)</b> Airflow at 2" Orifice: Waterlift at Sealed Orifice: Vacuum Motor Type: Vacuum Motor Amps Vacuum Motor Stages: Vacuum Motor Voltage: Vacuum Motor Watts:	<b>Vacuum</b>	<b>Blower</b>
	99 cfm 117.4 in (2982 mm) Tangential discharge; UL/CSA 10 A 3 stage 120V 1200 W	104 cfm 91 in (2311 mm) Tangential discharge; UL/CSA 8.6 A 2 stage 120V 1000 W
<b>Tank Capacity</b> Solution Tank Capacity: Recovery Tank Capacity:	15 gal (56.7 L) 19 gal (71.9 L)	
<b>Standard Accessories/Tools</b>	Double-bend aluminum wand (2-piece); 25 ft. (7.62M) recovery hose – Black; 25 ft. (7.62M) blower hose - Gray; 25 ft. (7.62M) high pressure hose with detachable variable pressure gun; Floor squeegee tool; Hand squeegee tool; Blower tool; Gulper floor drain tool; Metering tip packet; Fill Hose; 1 Gal. (3.78L) Formula 710 Multi-Surface Acid Cleaner; 2 Qt. (1.89L) Formula 720 Rinse	
<b>Power Cord</b> Power Cord Length: Power Cord Description:	25 ft (7.6 m); GFCI (120V, 15A, Class A) 14 gauge 3 wire SJTO; recognized by UL and CSA, safety yellow	
<b>Total Power Consumption</b>	120V, 14.25 amp	
<b>Dimensions</b> Product Height: Product Length: Product Width: Product Weight:	37.5 in (95.25 cm) 36.5 in (92.7 cm) 18.5 in (47 cm) 125.6 lb (57 kg) machine only; 142.4 lb (64.7 kg.) machine with accessories	
<b>Optional Accessories/Tools</b>	Carpet extraction floor tool, part number 600049	
<b>Warranty</b>	<b>10 years</b> – Nobles warrants the rotationally-molded polyethylene housings and parts on all of its machines to be free from defect in materials and workmanship, under normal use and service for ten ( <b>10</b> ) years to the original end user. <b>3 years</b> – Nobles guarantees the performance of non-polyethylene parts and components to be free from defects for up to three ( <b>3</b> ) years or 2,500 hours of operation. <b>3 years</b> – Labor charges are covered for three ( <b>3</b> ) full years from the date of purchase for Nobles/Tennant service provider is used for repair.	