

Strive™ with ReadySpace™

Dual Technology Carpet Cleaner



Features		Specifications (English/Metric)	
Product Number 9000503		ReadySpace	Restorative Extraction
Productivity			
Recommended cleaning speed		100 fpm / 30.5 mpm	50 fpm / 155 mpm
Maximum per hour		13,200 ft ² / hr – 1,226 m ² /hr	5,500 ft ² / hr – 510 m ² / hr
Typical range per hour		6,000-10,000 ft ² / hr 560-930 m ² /hr	2,000-4,000 sq ft / hr 185-370 m ² /hr
Chassis/Body Construction (Rotationally-molded polyethylene)			
Caster diameter		4 in / 10.16 cm	
Wheel diameter		8 in / 20.32 cm, non-marking neopren	
Solution System			
Solution tank capacity		21 gal / 72 L	
Nominal solution flow rate		.33 gpm – 1.3 l/m	1 gpm – 3.8 l/min
Solution pump		100 psi/6.9 bar	
Nozzle configuration		(2) quick release nozzles	
Recovery System			
Recovery tank capacity		21 gal – 72 L	
Vacuum shoe size		22 in/ 56 cm	23 in/ 58 cm
Airflow		65 cfm – 1.84 m3 per min	
Waterlift		120 in – 305 cm	
Vacuum motor HP		Two .64 HP – .48 KW vac motors	
Vacuum motor stages		3 stage	
Brush System			
Roller / brush length		22 in / 56 cm	
Roller / brush material		Nylon	
Motor HP		Two .625 HP / .315 KW	
Motor RPM		700 RPM	
Drive System			
Top transport speed		Up to 250 fpm / 76 mpm	



Strive™ with ReadySpace™

Dual Technology Carpet Cleaner



Features	Specifications (English/Metric)
Max. ramp while cleaning	3 degree
Max. ramp while transporting	11 degree
Transaxle HP	.2 HP / .104 KW continuous
Power & Electrical System	
System voltage	24 V
Total power consumption	65 amps
Battery run time (continuous cleaning rating)	2.5 hours
Battery configuration	4-6 volt 235 AH batteries
Roller / brush circuit breaker	17 A
Drive circuit breaker	20 A
Sound Level	72 dBa @ operator's ear
Dimensions	
Product height	42 in / 107 cm
Product length	60 in / 152 cm
Product width	28 in / 71 cm
Product weight	590 lb / 268 kg 340 lb / 154 kg (without batteries)
Optional Accessories	Floor wand, hand tool and hoses
Warranty	The warranty of this unit shall be a minimum of 10-years on rotationally-molded polyethylene housings and parts to be free from defects and workmanship under normal use and service. The non-polyethylene parts shall have a minimum of a three (3) year warranty under normal use and service. This unit shall also include service labor coverage of warranty items for a minimum of three (3) years.