



Commercial Floor Care Equipment

- Easiest to Use upright vacuum
- Unsurpassed Performance
- Integrated Family Design

UltraGlide & UltraGlide Dual Motor Lightweight Commercial Upright Vacuums

Features	Specifications																								
Model Names and Numbers: SMU = Single Motor Upright DMU = Dual Motor Upright	<table border="0"> <tr> <td>UltraGlide</td> <td>12" SMU</td> <td>614219</td> </tr> <tr> <td>UltraGlide</td> <td>15" SMU</td> <td>614220</td> </tr> <tr> <td>UltraGlide Dual Motor</td> <td>12" DMU</td> <td>614307</td> </tr> <tr> <td>UltraGlide Dual Motor</td> <td>15" DMU</td> <td>614221</td> </tr> <tr> <td>UltraGlide Dual Motor</td> <td>18" DMU</td> <td>614222</td> </tr> </table>	UltraGlide	12" SMU	614219	UltraGlide	15" SMU	614220	UltraGlide Dual Motor	12" DMU	614307	UltraGlide Dual Motor	15" DMU	614221	UltraGlide Dual Motor	18" DMU	614222									
UltraGlide	12" SMU	614219																							
UltraGlide	15" SMU	614220																							
UltraGlide Dual Motor	12" DMU	614307																							
UltraGlide Dual Motor	15" DMU	614221																							
UltraGlide Dual Motor	18" DMU	614222																							
Dimensions Product Height: Product Length: Product Widths: Product Weights (w/o cord): (pounds / kilograms) Product Weights (with cord): (pounds / kilograms) Handle Weight:	<table border="0"> <tr> <td>44 in / 112 cm</td> <td></td> <td></td> </tr> <tr> <td>13 in / 33 cm</td> <td></td> <td></td> </tr> <tr> <td>12 in / 30 cm</td> <td>15 in / 38 cm</td> <td>18 in / 46 cm</td> </tr> <tr> <td>12" SMU: 16.6 / 7.5</td> <td>15" SMU: 17.1 / 7.8</td> <td></td> </tr> <tr> <td>12" DMU: 17.9 / 8.1</td> <td>15" DMU: 18.4 / 8.3</td> <td>18": 19.2 / 8.7</td> </tr> <tr> <td>12" SMU: 18.8 / 8.5</td> <td>15" SMU: 19.3 / 8.8</td> <td></td> </tr> <tr> <td>12" DMU: 20.1 / 9.1</td> <td>15" DMU: 20.6 / 9.3</td> <td>18": 21.4 / 9.7</td> </tr> <tr> <td colspan="3">2.5 pounds / 1.1 kg for every model</td> </tr> </table>	44 in / 112 cm			13 in / 33 cm			12 in / 30 cm	15 in / 38 cm	18 in / 46 cm	12" SMU: 16.6 / 7.5	15" SMU: 17.1 / 7.8		12" DMU: 17.9 / 8.1	15" DMU: 18.4 / 8.3	18": 19.2 / 8.7	12" SMU: 18.8 / 8.5	15" SMU: 19.3 / 8.8		12" DMU: 20.1 / 9.1	15" DMU: 20.6 / 9.3	18": 21.4 / 9.7	2.5 pounds / 1.1 kg for every model		
44 in / 112 cm																									
13 in / 33 cm																									
12 in / 30 cm	15 in / 38 cm	18 in / 46 cm																							
12" SMU: 16.6 / 7.5	15" SMU: 17.1 / 7.8																								
12" DMU: 17.9 / 8.1	15" DMU: 18.4 / 8.3	18": 19.2 / 8.7																							
12" SMU: 18.8 / 8.5	15" SMU: 19.3 / 8.8																								
12" DMU: 20.1 / 9.1	15" DMU: 20.6 / 9.3	18": 21.4 / 9.7																							
2.5 pounds / 1.1 kg for every model																									
Chassis/Body Construction	Injection-molded Bayblend® (ABS and Polycarbonate) and ABS																								
Vacuum Noise Rating	69 dBA (operator)																								
Brush Drive System Brush Belt Description: Brush: Brush Motor Power (DMUs): Brush RPM	<p>Cogged / gear drive belt Dynamically balanced for lowest noise and vibration at high rpm. Chevron bristle design converges debris to the vacuum nozzle intake</p> <table border="0"> <tr> <td>12" & 15": 180 watts</td> <td>18": 200 watts</td> </tr> <tr> <td>SMUs & 18": 4500 rpm (avg.)</td> <td>12" & 15" DMUs: 5000 rpm</td> </tr> </table>	12" & 15": 180 watts	18": 200 watts	SMUs & 18": 4500 rpm (avg.)	12" & 15" DMUs: 5000 rpm																				
12" & 15": 180 watts	18": 200 watts																								
SMUs & 18": 4500 rpm (avg.)	12" & 15" DMUs: 5000 rpm																								
Vacuum System Airflow - Motor: Waterlift - Motor: Waterlift - Machine Vacuum Motor Type: Vacuum Motor Power: Vacuum Motor Hp:	<table border="0"> <tr> <td>92 cfm / 42 litres per second</td> </tr> <tr> <td>79 in / 2000 mm</td> </tr> <tr> <td>59 in / 1500 mm</td> </tr> <tr> <td>2-stage</td> </tr> <tr> <td>SMU: 850 watts</td> <td>DMU: 800 watts</td> </tr> <tr> <td>SMU: 1.14 hp</td> <td>DMU: 1.07 hp</td> </tr> </table>	92 cfm / 42 litres per second	79 in / 2000 mm	59 in / 1500 mm	2-stage	SMU: 850 watts	DMU: 800 watts	SMU: 1.14 hp	DMU: 1.07 hp																
92 cfm / 42 litres per second																									
79 in / 2000 mm																									
59 in / 1500 mm																									
2-stage																									
SMU: 850 watts	DMU: 800 watts																								
SMU: 1.14 hp	DMU: 1.07 hp																								
Debris Recovery / Filtration Vacuum Bag Capacity: Vacuum Bag Description: Vacuum Filtration:	<p>4.5 liter / 4.8 quart (1.2 gallon) Three-ply paper micro filter bag with "Bag Full / Blockage" indicator light Standard Five-level Filtration: Three-ply paper filter bag, washable foam intake filter, 3M Filtrete®, exhaust microfilter together yield 98% @ 0.3 micron size filtration Optional HEPA motor intake filter rated at 99.97% efficient at 0.3 micron size</p>																								
Recovery System Vacuum Hose Length: Vacuum Wand:	<table border="0"> <tr> <td>15 in / 38 cm stretches to 63 in / 160 cm</td> </tr> <tr> <td>Telescopic (21" / 53 cm to 35" / 89 cm) 1-piece wand – 1 ¼ inch / 32 mm I.D. diam.</td> </tr> </table>	15 in / 38 cm stretches to 63 in / 160 cm	Telescopic (21" / 53 cm to 35" / 89 cm) 1-piece wand – 1 ¼ inch / 32 mm I.D. diam.																						
15 in / 38 cm stretches to 63 in / 160 cm																									
Telescopic (21" / 53 cm to 35" / 89 cm) 1-piece wand – 1 ¼ inch / 32 mm I.D. diam.																									
Power Cord Power Cord Length: Power Cord Type:	<table border="0"> <tr> <td>49 ft / 15 m</td> </tr> <tr> <td>17 gauge, 3 wire SJT, Safety Yellow, UL-listed</td> </tr> </table>	49 ft / 15 m	17 gauge, 3 wire SJT, Safety Yellow, UL-listed																						
49 ft / 15 m																									
17 gauge, 3 wire SJT, Safety Yellow, UL-listed																									
Standard Accessories	Telescopic wand, wand handle with suction control, 4:1 stretch hose, crevice tool, dusting brush, spare paper filter bag																								
Warranty	<p>A one-year warranty is extended to the original end user against manufacturing defects and workmanship on non-wear components for these machines. A three-year limited warranty against materials and workmanship on motors and belts (not due to normal usage / carbon brush wear)</p>																								
Certifications	ETL (UL & CSA equivalent), CRI Green Label																								

